





## RM/IB Dimensions

Model	Max. cap. litres	Milkings	A mm	B* mm	C mm	D mm	E mm	F** mm	G mm	H mm	I mm	Legs number	Weight kg
1600	1678	2	2185	2766	952	1302	1895	1825 - 1945	547	445	572	4	464
2200	2237	2	2818	3399	952	1302	1264	1825 - 1945	547	445	888,5	4	584
2800	2813	2	2009	2590	1440	1800	860	2179 - 2299	604	445	492,5	6	682
3300	3367	2	2350	2931	1440	1800	1030	2179 - 2299	604	450	654,5	6	750
3800	3881	2	2665	3246	1440	1800	1188	2179 - 2299	604	450	812	6	830
4400	4484	2	3035	3616	1440	1800	1373	2179 - 2299	604	450	997	6	980
5000	5039	2	3374	3955	1440	1800	1029	2179 - 2299	604	450	1167	8	1076
6000	6148	2	4000	4581	1440	1800	1236,5	2173 - 2293	604	450	687,5	8	1240

Model	Max. cap. litres	Milkings	A mm	B* mm	C mm	D mm	E mm	F** mm	G mm	H mm	I mm	Legs number	Weight kg
1600	1678	4/6	2185	2766	952	1302	1895	1630 - 1750	372	445	572	4	429
2200	2237	4/6	2818	3399	952	1302	1264	1630 - 1750	372	445	888,5	6	525
2800	2813	4/6	2009	2590	1440	1800	860	1996 - 2116	409	445	492,5	6	601
3300	3367	4/6	2349	2930	1440	1800	1030	1996 - 2116	409	450	654,5	6	655
3800	3881	4/6	2665	3246	1440	1800	1188	1996 - 2116	409	450	812	6	730
4400	4484	4/6	3033	3614	1440	1800	1372	1996 - 2116	409	450	997	6	860
5000	5039	4/6	3374	3955	1440	1800	1028	1996 - 2116	409	450	1167	8	940
6000	6148	4/6	3374	3955	1440	1800	1028	2269 - 2389	409	450	687,5	8	1050
7150	7320	4/6	4000	4581	1440	1800	1236,5	2269 - 2389	409	450	687,5	8	1300

\*With ECO-WASH: B + 190 mm.

\*\*With tank guard Oculus: F + 25 mm.

F = min. and max. height of leg screw when tank is installed completely horizontal

Available in 2, 4 & 6 Milkings and for AMS milking.

RM/IB 1600-5000 2-6 milkings and RM/IB 6000 4 milkings:

1 agitator incorporating 1 rotojet spray ball.

RM/IB 6000 2 milkings and RM/IB 7150 4-6 milkings:

2 agitators incorporating 4 rotojet spray balls.

Subject to modifications. The photographs and descriptions provided are intended as a guide and may not always exactly match the items supplied.

